

§ 250.921

(d) The BSEE may require you to conduct a platform design basis check when the reduced environmental loading criteria contained in API RP 2A-WSD Section 17.6 are not applicable.

(e) By November 1, 2009, you must submit a complete list of all the platforms you operate, together with all the appropriate data to support the assessment category you assign to each platform and the platform assessment initiators (as defined in API RP 2A-WSD) to the Regional Supervisor. You must submit subsequent complete lists and the appropriate data to support the consequence-of-failure category every 5 years thereafter, or as directed by the Regional Supervisor.

(f) The use of Section 17, Assessment of Existing Platforms, of API RP 2A-WSD is limited to existing fixed structures that are serving their original approved purpose. You must obtain approval from the Regional Supervisor for any change in purpose of the platform, following the provisions of API RP 2A-WSD, Section 15, Re-use.

§ 250.921 How do I analyze my platform for cumulative fatigue?

(a) If you are required to analyze cumulative fatigue on your platform because of the results of an inspection or platform assessment, you must ensure that the safety factors for critical elements listed in § 250.908 are met or exceeded.

(b) If the calculated life of a joint or member does not meet the criteria of § 250.908, you must either mitigate the load, strengthen the joint or member, or develop an increased inspection process.

Subpart J—Pipelines and Pipeline Rights-of-Way

§ 250.1000 General requirements.

(a) Pipelines and associated valves, flanges, and fittings shall be designed, installed, operated, maintained, and abandoned to provide safe and pollution-free transportation of fluids in a manner which does not unduly interfere with other uses in the Outer Continental Shelf (OCS).

(b) An application must be accompanied by payment of the service fee listed in § 250.125 and submitted to the

30 CFR Ch. II (7–1–13 Edition)

Regional Supervisor and approval obtained before:

(1) Installation, modification, or abandonment of a lease term pipeline;

(2) Installation or modification of a right-of-way (other than lease term) pipeline; or

(3) Modification or relinquishment of a pipeline right-of way.

(c)(1) Department of the Interior (DOI) pipelines, as defined in § 250.1001, must meet the requirements in §§ 250.1000 through 250.1008.

(2) A pipeline right-of-way grant holder must identify in writing to the Regional Supervisor the operator of any pipeline located on its right-of-way, if the operator is different from the right-of-way grant holder.

(3) A producing operator must identify for its own records, on all existing pipelines located on its lease or right-of-way, the specific points at which operating responsibility transfers to a transporting operator.

(i) Each producing operator must, if practical, durably mark all of its above-water transfer points by April 14, 1999, or the date a pipeline begins service, whichever is later.

(ii) If it is not practical to durably mark a transfer point, and the transfer point is located above water, then the operator must identify the transfer point on a schematic located on the facility.

(iii) If a transfer point is located below water, then the operator must identify the transfer point on a schematic and provide the schematic to BSEE upon request.

(iv) If adjoining producing and transporting operators cannot agree on a transfer point by April 14, 1999, the BSEE Regional Supervisor and the Department of Transportation (DOT) Office of Pipeline Safety (OPS) Regional Director may jointly determine the transfer point.

(4) The transfer point serves as a regulatory boundary. An operator may write to the BSEE Regional Supervisor to request an exception to this requirement for an individual facility or area. The Regional Supervisor, in consultation with the OPS Regional Director and affected parties, may grant the request.